



CONVEYCO

(PTY) LTD

PLANNED MOVEMENT
KEEPING YOUR SUPPLY CHAIN ON TRACK

Conveyor Rollers



Various types of rollers & idlers

Conveyco was established in 1977 and are market leaders in the manufacturing of rollers like gravity rollers, powered rollers, stainless steel rollers, head & tail pulleys to idlers.

We aim to supply competitively priced, high quality rollers.

Conveyco rollers are manufactured with precision bearings in mild steel or stainless steel tubes.

All mild steel tubes are electro-galvanized at our in-house electroplating division.

We offer extensive customer service for roller repair and maintenance services.

With our many years of experience we gladly offer any advice to assist the customer in making the right decision on which type of roller to use in their specific industry.

We value our customers and aim for a long term relationship through excellent service.



Roller sleeves & coverings



Various Tapper Rollers



Various Shafts

Roller Types & Specifications												
Pipe OD (mm)	Pipe Material	Wall Thickness (mm)	Shaft Diameter (mm)	Carrying capacity / roller 600mm long with UDL load (kg)	End cap material	Sealed bearing	Non-sealed	Precision	Non-precision	Dust cover	Bearing type	Operating Temp. (Degrees Celcius)
20	PVC	1.5	6	Depends on length	plastic		*		*		Stainless steel ball bearings	02 to 40
25.4	MS	1.2	8	10	steel		*		*		Mild steel ball bearings	Minus 25 to +75 if **2
30	PVC	1.8	8	Depends on length	plastic		*		*		Stainless steel ball bearings	02 to 40
31.8	MS	1.2	8	15	steel		*		*		Mild steel ball bearings	Minus 25 to +75 if **2
38.1	MS	1.2	10/11/12 md	25	steel		*		*		Mild steel ball bearings	Minus 25 to +75 if **2
38.1	MS	1.2	8/10/12 rmd	25	Nylon	*		*		*	6002 2RS Bearing	02 to 50
42	MS	2.5	10/12 md	30	steel		*		*		Mild steel ball bearings	Minus 25 to +75 if **2
50.8	MS or SS or ALU	1.6/1.5	10r/ 12r / 11 hex	50	Nylon	*		*		*	6002 2RS Bearing	02 to 50
50.8	MS or SS or ALU	1.6/1.5	10 md	40	Nylon bush		*		*		No bearing, just the bush	02 to 40
50.8	MS or SS or ALU	1.6/1.5	10 md	50	Acetyl housing		*		*		Stainless steel ball bearings	minus 25 to +75
50.8	MS or SS or ALU	1.6/1.5	10/11/12 md	50	steel		*		*		Mild steel ball bearings	Minus 25 to +75 if **2
50	PVC	2.8	10 md	Depends on length	plastic		*		*		Stainless steel ball bearings	02 to 40
57	MS	2	12 md	100	steel	*		*			6002 2RS Bearing	Minus 25 to +75 if **2
60.3	MS	2	12 md	100	steel	*		*			6002 2RS Bearing	Minus 25 to +75 if **2
60.3	MS	2	8/10/12/14/20 rmd	70-150	Nylon	*		*		*	6002 2RS Bearing	02 to 40
63.5	MS	2.0-3.0	12 md	100	steel	*		*			6002 2RS Bearing	Minus 25 to +75 if **2
63.5	MS	2.5	8/10/12/14 rmd	70-120	Nylon	*		*		*	6002 2RS Bearing	02 to 40
76	MS	3	15/20 md	200 & 500	steel	*		*			6005 2RS Bearing	Minus 25 to +75 if **2
76	MS	3	16/20 md	up to 250	Nylon	*		*		*	6005 2RS Bearing	02 to 40
89	MS	3	20 md	300	steel		*		*		Mild steel ball bearings	Minus 25 to +75 if **2
101	MS	3	25 md	250	Nylon	*		*		*	2RS Bearing	02 to 40
**2												
If low or high temp grease is used (either or)												
MS												
SS												
ALU												
ALU												
Yellow =				most popular								



Various Rollers



Slatted Pulley & Trough Rollers



Gravity Rollers



Stainless Steel Bend Rollers



Gravity Rollers

Conveyco (Pty) Ltd

17 Range Road /
PO Box 111
Blackheath
Cape Town
7580

Tel: +27 (0) 21 905 0230
Fax: +27 (0) 21 905 0236
E-mail: neil@conveyco.co.za
Website: www.conveyco.co.za
Registration No. 1959/004758/07



CONVEYCO

(PTY) LTD

PLANNED MOVEMENT
KEEPING YOUR SUPPLY CHAIN ON TRACK